





Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel: +381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg

www.tisab.rs



www.ipkamere.com

www.tisab-inzenjering.rs

KOMPLET 1 - PENTABRID NXVR-104H 4-KANALNI I 4 DOME KAMERE 1MPIX 89 EUR + PDV

 NORA NXVR-104H	<p>5-U-1 SNIMAAČ: AHD/CVI/TVI/IP/Analog 4CH, Network, 1 x SATA, P2P HDMI, VGA, USB, Audio DIY Video Input: HD includes AHD, HD-CVI, HD-TVI HD: Max 4CH@25fps / IPC: Max 9CH@30fps / Analog: Max 4CH@30fps Video Output: 1xHDMI/1xVGA/1xCVBS Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 HD: 1080N/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-25fps adjustable; Analog: 960H, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P (Total incoming bandwidth 546M), PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 1080P/720P Playback: Support single channel mode. Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support Internet Explorer and Special Client Software 2xUSB : 1xRJ45(10M/100M adaptive Ethernet interface) 1 SATA Hard Disk Interface (2.5"/3.5" SATA, Up to 6TB) Backup: USB2.0 (such as U disk, USB Drive) and network Support remote view by Mobilephone (iPhone, iPad, Android Phone) Standard Color: White Optional Color: Black (Model XVR2004PDB) Power consumption: DC 12V 56W (Without Hard Disk) Dimensions (LxWxH): 215x215x53(mm) Weight: 2kg</p>	<p>1 KOM</p> <p>89 EUR + PDV</p>
 NC-10FDP NORA	<p>NC-10FDP 1/4" OV 1.0MP CMOS Sensor, 720P, With IR-CUT, DNR , Plastic IR Dome Camera IR LED: 14μ x 18PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: 90.5(W) x 80(H) x 80(D)mm Weight: 300g</p>	<p>4 KOM</p>

KOMPLET 2 - PENTABRID NXVR-104H 4-KANALNI I 4 BULLET KAMERE 1MPIX 92 EUR + PDV







 NORA NXVR-104H	<p>5-U-1 SNIMAAČ: AHD/CVI/TVI/IP/Analog 4CH, Network, 1 x SATA, P2P HDMI, VGA, USB, Audio DIY Video Input: HD includes AHD, HD-CVI, HD-TVI HD: Max 4CH@25fps / IPC: Max 9CH@30fps / Analog: Max 4CH@30fps Video Output: 1xHDMI/1xVGA/1xCVBS Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 HD: 1080N/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-25fps adjustable; Analog: 960H, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P (Total incoming bandwidth 546M), PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 1080P/720P Playback: Support single channel mode. Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support Internet Explorer and Special Client Software 2xUSB : 1xRJ45(10M/100M adaptive Ethernet interface) 1 SATA Hard Disk Interface (2.5"/3.5" SATA, Up to 6TB) Backup: USB2.0 (such as U disk, USB Drive) and network Support remote view by Mobilephone (iPhone, iPad, Android Phone) Standard Color: White Optional Color: Black (Model XVR2004PDB) Power consumption: DC 12V 56W (Without Hard Disk) Dimensions (LxWxH): 215x215x53(mm) Weight: 2kg</p>	<p>1 KOM</p> <p>92 EUR + PDV</p>
 NC-10FBP	<p>NC-10FBP 1/4" OV 1.0MP CMOS senzor, 720P, sa IR-CUT, DNR , plastična Weatherproof IR kamera IR LED diode: 14μ x 18PCS Domet IR dioda: 20M Board Len 2.8mm/F2.0 stepen zaštite: IP66 Nosaač sa 3-ose rotacije i zaštitom od sečenja kabla Dimenzije: 160.8(W) x 62(H) x 62(D)mm Težina: 380g</p>	<p>4 KOM</p>









Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd
Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg


www.tisab.rs
www.ipkamere.com
www.tisab-inzenjering.rs

**KOMPLET 3 - DVR LS-9604PD (ILI HB7204KL) 4-KANALNI 960H I 4 BULLET KAMERE 700 TVL
79 EUR + PDV**

 	<p>LS-9604PD</p>	<p>LS-9604PD Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF: 352x240 with 120 Fps (NTSC); 352x288 with 100 Fps (PAL) D1: 720x480 with 120 Fps (NTSC); 704x576 with 100 Fps (PAL) 960H: 960x480 with 120 Fps (NTSC); 960x576 with 100 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software 2 x USB 1 SATA Hard Disk interface (2.5/3.5' SATA, Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone 960H*4CH, Network Standard Color: White Optional Color: Black (Model LS-9604PDB) VGA, USB Backup, USB Mouse Dimensions (LxWxH): 215*215*53(mm) weight: 2kg</p>	<p>1 KOM</p>
		<p>79 EUR + PDV</p>	
 	<p>HB7204KL (OPCIONO)</p>	<p>HB7204KL 4-kanalni DVR, snimanje sva 4 kanala u 960H rezoluciji. 1 SATA HD (nije uključen). Playback 4 kanala simultano. Mini 1H kucište, 2 audio ulaza/1 izlaz; 4 alarmna ulaza/1 izlaz; 4 zone za maskiranje; Izlazi: HDMI, VGA, CVBS; napajanje 12V DC/24W; P2P, Android/iphone besplatan softver za daljinski pristup. Cloud servis za povezivanje sa uređajem preko Interneta jednostavnim skeniranjem QR koda pomoću kamere na mobilnom telefonu.</p>	
 	<p>LICE24NSHE</p>	<p>LICE24NSHE Color 1/3" SONY 700TVL, Low Illumination, ATR, ugrađen OSD meni, DNRSony 672/673 + Sony Effio-e Infracrvene diode: 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0Vodootporna: IP663-ose kabl u nosaču DIMENZIJE: 86(Š) x60(V) x55(D)mm TEŽINA: 400g</p>	<p>4 KOM</p>

**KOMPLET 4 - DVR LS-9604PK (ILI LS-9608K) 8-KANALNI 960H I 8 BULLET KAMERA 700 TVL
163 EUR + PDV**

  <p>960H*8CH, Network VGA, USB Backup, USB Mouse</p>	<p>LS-2008PD (LS-9608K)</p>	<p>LS-2008PD Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) D1:720x480 with 240 Fps (NTSC); 704x576 with 200 Fps (PAL) 960H:960x480 with 240 Fps (NTSC); 960x576 with 200 Fps (PAL) Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software 2 x USB 1 SATA Hard Disk interface (2.5/3.5' SATA, Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone Standard Color: White Optional Color: Black (Model LS-2008PDB) Dimensions (LxWxH): 215*215*53(mm) težina: 2kg</p>	<p>1 KOM</p>
		<p>163 EUR + PDV</p>	
 	<p>LS-9508PD (LS-9604PK)</p>	<p>LS-9508PD Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out Audio Input/Output: RCA 2CH In/ 1CH Out Compression Method: H.264 Real time recording support: CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) D1:720x480 with 240 Fps (NTSC); 704x576 with 200 Fps (PAL) 960H:960x480 with 240 Fps (NTSC); 960x576 with 200 Fps (PAL) Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); Playback resolution: D1 x 4 Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback 1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software 2 x USB 1 SATA Hard Disk interface (2.5/3.5' SATA, Up to 4TB) Backup: USB2.0 and Network Support remote view by Mobilephone D1*8CH, Network Standard Color: White Optional Color: Black (Model LS-9508PDB) VGA, USB Backup, USB Mouse Dimenzije (LxWxH): 215*215*53(mm) težina: 2kg</p>	
 	<p>LICE24NSHE</p>	<p>LICE24NSHE Color 1/3" SONY 700TVL, Low Illumination, ATR, ugrađen OSD meni, DNRSony 672/673 + Sony Effio-e Infracrvene diode: 5X24komada domet IC dioda: 20M Optika na ploči 3.6mm/F2.0Vodootporna: IP663-ose kabl u nosaču DIMENZIJE: 86(Š) x60(V) x55(D)mm TEŽINA: 400g</p>	<p>4 KOM</p>

 			
<p>Tisab d.o.o. ul. Tošin Bunar 143 (Studentski grad, I blok - krilo G) 11070 Novi Beograd Tel:+381 11 3103-999, fax. +381 11 214-64-34, mob. +381 64 87-515-12 e-mail: zarko@tisab.rs, skype: tisab-bg</p>		<p>www.tisab.rs</p> <p>www.ipkamere.com</p> <p>www.tisab-inzenjering.rs</p>	
<p>KOMPLET 5 - DVR LS-9604PD (ILI HB7204KL) 4-KANALNI 960H I 4 BULLET KAMERE 1200 TVL 207 EUR + PDV</p>			
 <p>NOVO 1200 TVL</p>	<p>LIZM40SFS (LIP40SHE)</p>	<p>LIZM40SFS "1/3"" SONY 1.4MP CMOS Senzor, 720P, 1200TVL, Low Illumination IR-CUT, DNR" IR LED: ϕ 5X42PCS Domet IR dioda: 40M 2.8-12mm Optika sa ručnim podešavanjem zuma (2M Pixels) Vodootporna: IP66 Anti-Cut Nosač sa 3-ose rotacije DC12V Dimenzije: 290(W) x 92(H) x 80(D)mm Težina: 1.85KG</p>	<p>207 EUR + PDV</p> <p>4 KOM</p>
<p>KOMPLET 6 - DVR LS-9604PK (ILI LS-9608K) 8-KANALNI 960H I 8 BULLET KAMERA LIP40SHE 1200 TVL 328 EUR + PDV</p>			
<p>KOMPLET 7 - TRIBRIDNI 4-KANALNI SNIMAČ NCR-5104D I 4 DOME VANDAL VARIFOKAL KAMERA 2MPIX CVI 189 EUR + PDV</p>			
 <p>1080P</p>	<p>NCR-5104D</p>	<p>NCR-5104D tribridni FULL HD snimač 4 kanala Video Input: CVI: 4CHx1080P / IPC: Max 2CHx1080P / Analog: 4CHx960H/4CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 1080P, PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable; HDCVI: 720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Analog: 960HD1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Preview resolution: 720P (1280*720) /1080P(1920*1080) Single/Multi-channel playback: 1/4CHx720P@30fps, 1/4CHx1080P@15fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support IE and special client software 1 SATA Hard Disk Interface (Up to 4TB); 2xUSB (1 Rear); 1xRJ45; Backup: USB2.0 (such as U disk, mobile hard disk, USB Drive) and network Tribrid: 2CH HDCVI & 2CH IP Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone) 4CH, Network, 1 x SATA, P2P DC12V \leq15W(With adaptor, without hard disk) HDMI, VGA, USB Backup, USB Mouse Dimensions (LxWxH): 335*270*55(mm) Weight: 2.5kg 1080P</p>	<p>189 EUR + PDV</p> <p>1 KOM</p>
	<p>NC-21VFD</p>	<p>NC-21VFD HD-CVI vandal dome kamera PAL 1/2.9 SONY 2.4MP CMOS Sensor 1080P With IR-CUT Low Illumination WDR DNR UTC 2.8-12mm Manual Zoom Lens brilliant white; Vandalproof IR Dome Camera IR LED: ϕ 5 (12μ) x 36PCS IR range: 30M 2.8-12mm Manual Zoom Lens Size: 125(W) x 105.8(H) x 135(D) mm Weight: 800g</p>	<p>4 KOM</p>
<p>KOMPLET 8 - TRIBRIDNI 8-KANALNI SNIMAČ NCR-5208D I 8 DOME VANDAL VARIFOKAL KAMERA NC-21VFD 2MPIX CVI 349 EUR + PDV</p>			
 <p>1080P</p>	<p>NCR-5208D</p>	<p>NCR-5208D Video Input: CVI: 8CHx1080P / IPC: Max 4CHx1080P / Analog: 8CHx960H/8CHxD1 Video Output: VGA 1CH Out/ HDMI 1CH Out Audio Input/Output: RCA 1CH In/ 1CH Out Compression Method: H.264 HDCVI: 1080P, PAL every channel 1fps-12fps adjustable; NTSC every channel 1fps-15fps adjustable; HDCVI: 720P, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; Analog: 960HD1, PAL every channel 1fps-25fps adjustable; NTSC every channel 1fps-30fps adjustable; IPC: 1080P/960P/720P, PAL every channel 1fps-25fps adjustable; Preview resolution: 720P (1280*720) /1080P (1920*1080) Single/Multi-channel playback: 1/4/8CHx720P@30fps, 1/4/8CHx1080P@15fps Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating Static, Dynamic IP and DDNS, P2P, Support IE and special client software 2 SATA Hard Disk interface (Up to 8TB); 2xUSB (1 Rear); 1xRJ45 Backup: USB2.0 (such as U disk, mobile hard disk, USB drive) and Network Tribrid: 4CH HDCVI & 4CH IP Support remote view by Mobilephone (iPhone, iPad, Android, Windows Phone) 8CH, Network, 2 x SATA, P2P DC12V \leq15W (With adaptor, without hard disk) HDMI, VGA, USB Backup, USB Mouse Dimensions (LxWxH): 335*270*55(mm) Weight: 2.5kg</p>	<p>349 EUR + PDV</p> <p>1 KOM</p>